

View Online at <https://aerobasegroup.com/nsn/6625-01-113-5993>

Circuit Current For Which Designed:

Ac or dc

Overall Depth:

4.750 inches

Overall Length:

7.500 inches

Overall Width:

6.500 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration proof

Furnished Items And Quantity:

Case, vinyl carrying 1; lead, test 3; rod, ground 2; calibration standard, plug in 3 way 1

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

Internal

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+500.0 ohms single indicator single range

Scale Selection Method:

Switch

Features Provided:

Internal battery accommodation and portable

Circuit Attachment Method And Quantity:

3 connector, plug and 3 connector, receptacle and 3 solder lug

Special Features:

Ruggedized

Special Markings:

Mark top part of scale 0, .5, 1, 5, 10, 50, 100 and 500; mark bottom part of scale left side resistance symbol; bottom right side capacitor symbol

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Portable

Supplementary Features:

Built in probe res check; built in battery check; log type scale

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0