

View Online at <https://aerobasegroup.com/nsn/6625-01-115-1051>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Mounting Hole Diameter:**

0.125 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

36.0 volts

**Dial Scale Marking Color:**

Green single indicator single range and black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.250 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0, 24, 36

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Operating Voltage Rating In Volts:**

24.0 dc

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0