# NSN 6625-01-115-4090

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-115-4090

# Circuit Current For Which Designed:

Dc

# Dielectric Withstanding Voltage In Volts:

3000.0

# **Overall Length:**

2.030 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

## 1.871 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.871 inches

## **Overall Height:**

2.375 inches

## Overall Width:

2.809 inches

## Scale Division Quantity:

# 60 single indicator single range

Mounting Stud Length:

#### 0.465 inches

## **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

## Furnished Items And Quantity:

Nut 6; lockwasher 6; flat washer 2; seal 1

## Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

#### Sensitivity Rating:

6.0 amperes

#### Dial Scale Marking Color:

Black single indicator single range

#### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

## Meter Depth Behind Mounting Flange:

# 1.115 inches

## Meter Body Diameter Behind Mounting Flange:

2.151 inches

#### Movement Type:

Moving coil, permanent magnet

## Background Color:

White single indicator single range

# NSN 6625-01-115-4090

Ammeter - Page 2 of 2



**Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+6.0 amperes, dc single indicator single range Mounting Stud Diameter: 0.109 inches **Scale Selection Method:** Terminal **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized Material: Plastic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A310a0