

View Online at <https://aerobasegroup.com/nsn/6625-01-115-4305>

Circuit Current For Which Designed:

Dc

Overall Length:

2.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

Overall Height:

2.270 inches

Overall Width:

2.990 inches

Scale Division Quantity:

12 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Airtight and cold resistant and corrosion resistant and dust resistant and fire resistant and fungus resistant and hermetic and heat resistant and humidity resistant and salt spray resistant and salt water resistant and shock resistant and submersible and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 6; lockwasher 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.300 inches

Meter Body Diameter Behind Mounting Flange:

2.140 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; .75; 1.50; 2.25; 3.0

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0