

View Online at <https://aerobasegroup.com/nsn/6625-01-118-1682>

Circuit Current For Which Designed:

Dc

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Environmental Protection:

Shock resistant and vibration resistant and water resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator 2nd range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

0.775 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

First range -20; -10; -7; -5; -3; -2; -1; 0; +1; +2; +3; second range 0; 20; 40; 60; 80; 100

Scale Graduation Type:

Nonlinear single indicator all ranges

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets requirements of ansi c39.1

Style Designator:

Fan shape flush mtg

Supplementary Features:

Int res 730 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0