

View Online at <https://aerobasegroup.com/nsn/6625-01-118-1683>

Circuit Current For Which Designed:

Dc

Overall Length:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.062 inches

Meter Body Diameter Behind Mounting Flange:

2.187 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+20.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

115.0 ac

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0