

View Online at <https://aerobasegroup.com/nsn/6625-01-121-9594>

Circuit Current For Which Designed:

Ac

Overall Length:

2.220 inches

Overall Height:

2.730 inches

Overall Width:

3.150 inches

Scale Division Quantity:

50 single indicator 1st range

Mounting Stud Length:

0.450 inches

Environmental Protection:

Shock resistant and vibration proof

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 3; washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Red single indicator 2nd range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.010 inches

Meter Body Diameter Behind Mounting Flange:

2.190 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+50.0 volts, ac single indicator 1st range

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Int res 50 ohms

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0