

View Online at <https://aerobasegroup.com/nsn/6625-01-121-9596>

Circuit Current For Which Designed:

Dc

Overall Length:

2.220 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.698 inches

Overall Height:

2.730 inches

Overall Width:

3.150 inches

Scale Division Quantity:

50 single indicator 1st range

Mounting Stud Length:

0.500 inches

Shortest Horizontal Distance Between Mounting Centers:

1.095 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Red single indicator 3rd range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.010 inches

Meter Body Diameter Behind Mounting Flange:

2.190 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+4.0 amperes, ac single indicator 3rd range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Plus sign beneath positive terminal

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0