

View Online at <https://aerobasegroup.com/nsn/6625-01-121-9596>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.220 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.190 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.698 inches

**Overall Height:**

2.730 inches

**Overall Width:**

3.150 inches

**Scale Division Quantity:**

50 single indicator 1st range

**Mounting Stud Length:**

0.500 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.095 inches

**Furnished Items And Quantity:**

Nut 5; washer 5

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud triangular

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Red single indicator 3rd range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.010 inches

**Meter Body Diameter Behind Mounting Flange:**

2.190 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+4.0 amperes, ac single indicator 3rd range

**Mounting Stud Diameter:**

0.112 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Plus sign beneath positive terminal

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0