

View Online at <https://aerobasegroup.com/nsn/6625-01-123-2099>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.050 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

50 single indicator single range

Overall Diameter:

4.500 inches

Mounting Bolt Circle Diameter:

4.124 inches

Furnished Items And Quantity:

Nut 8; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

3.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

6 screw and 6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 microamperes, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

P sign and sealed do not open on back of meter

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0