

View Online at <https://aerobasegroup.com/nsn/6625-01-123-7976>

Circuit Current For Which Designed:

Dc

Overall Length:

1.630 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-50.0/+50.0 microamperes, dc single indicator single range

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

Int res 730 ohms porm 10 pct

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0