

View Online at <https://aerobasegroup.com/nsn/6625-01-124-2597>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.630 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

40 single indicator single range

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 2; washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.500 inches

**Meter Body Diameter Behind Mounting Flange:**

2.150 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+20.0 microamperes, dc single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Sealed do not open on back

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Internal impedance 3000 ohms porm 1 pct at 25 degrees centigrade; coil operating voltage 1000 vdc with respect to ground

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0