NSN 6625-01-124-4161

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-124-4161

Circuit Current For Which Designed:
Dc
Overall Length:
1.562 inches
Mounting Hole Diameter:
0.156 inches
Scale Division Quantity:
40 single indicator single range
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.125 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.250 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.750 inches
2.750 inches
2.750 inches Mounting Facility Type And Quantity:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg Shelf Life:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg Shelf Life: N/a
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg Shelf Life: N/a
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
2.750 inches Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+40.0 volts, dc single indicator single range Features Provided: Zero adjuster Circuit Attachment Method And Quantity: 1 threaded stud Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: