

View Online at <https://aerobasegroup.com/nsn/6625-01-126-3156>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

Between 1.930 inches and 1.970 inches

Overall Height:

Between 2.350 inches and 2.390 inches

Overall Width:

Between 2.540 inches and 2.580 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.420 inches

Meter Body Diameter Behind Mounting Flange:

0.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

1 bezel and 1 collar

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+100.0 decibels single indicator 1st range-20.0/+3.0 decibels above or below one milliwatt single indicator 2nd range-10.0/+13.0 decibels above or below one milliwatt single indicator 3rd range+0.0/+23.0 decibels above or below one milliwatt single indicator 4th range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Top three scales; dbm; 1st scale: 0, +10, +20, +23; 2nd: -10, 0, +10, +13; 3rd: -20, -10, 0, +3; 4th: rfdb; 0, 20, 40, 60, 80, 100

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0