

View Online at <https://aerobasegroup.com/nsn/6625-01-126-6936>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

5.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.469 inches

Overall Height:

4.281 inches

Overall Width:

4.250 inches

Scale Division Quantity:

50 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.594 inches

Meter Body Diameter Behind Mounting Flange:

4.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+50.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.234 inches

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

50.0 dc

Material:

Plastic and copper alloy

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0