NSN 6625-01-126-7906

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-126-7906

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

Between 1.734 inches and 1.766 inches

Overall Width:

Between 1.734 inches and 1.766 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

10 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Hex or square nut 4, lock washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

NSN 6625-01-126-7906

Voltmeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-1.5/+1.5 volts, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Anodize
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0