

View Online at <https://aerobasegroup.com/nsn/6625-01-129-0003>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Overall Height:

2.312 inches

Overall Width:

2.312 inches

Scale Division Quantity:

60 single indicator all ranges

Mounting Stud Length:

0.500 inches

Mounting Bolt Circle Diameter:

2.656 inches

Furnished Items And Quantity:

Nut 8; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts and 30.0 volts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.188 inches

Meter Body Diameter Behind Mounting Flange:

2.188 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+30.0 volts, dc single indicator 2nd range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Ruggedized per mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0