

View Online at <https://aerobasegroup.com/nsn/6625-01-129-2070>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.890 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.736 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.370 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.530 inches

Environmental Protection:

Dustproof and heat resistant and shock resistant and splash proof and vibration resistant and watertight

Shortest Horizontal Distance Between Mounting Centers:

1.368 inches

Furnished Items And Quantity:

Nut 9; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

300.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.610 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+300.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Features:

Indi true rms value

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0