

View Online at <https://aerobasegroup.com/nsn/6625-01-129-7919>

Overall Length:

11.250 inches

Overall Height:

5.250 inches

Overall Width:

11.250 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

Electronic test equipment

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Top of cabinet/counter

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

0.0 megahertz operating channel and 50.0 megahertz operating channel

Signal Voltage Rating Per Channel:

10.000 volts output

Pulse Duration Per Channel:

0.00002 milliseconds operating channel and 200.00000 milliseconds operating channel

Pulse Rise Time Per Channel:

5.000 nanoseconds operating channel

Pulse Decay Time Per Channel:

5.000 nanoseconds operating channel

Pulse Peak Amplitude Per Channel:

10.000 volts operating channel

Signal Data Type Per Channel:

Operating channel pulse

Output Wave Shape:

Pulse, variable width and pulse, gate and pulse, trigger

Operating Ac Frequency In Hertz:

50.0 2nd voltage and 400.0 2nd voltage

External Ac Operating Voltage In Volts:

216.0 2nd voltage and 250.0 2nd voltage

Special Features:

Adjustable pulse upper and lower levels; selectable source impedance - 50 ohm termination; fixed ttl outputs; independent rate, width and delay control; four pulse outputs - fixed ttl level sync, ttl, ttl w bar over, and variable amplitude; full 10 volt output; 5 nanoseconds rise/fall times

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200