

View Online at <https://aerobasegroup.com/nsn/6625-01-129-7919>

**Overall Length:**

11.250 inches

**Overall Height:**

5.250 inches

**Overall Width:**

11.250 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Average Life Measurement:**

Not rated

**End Application:**

Electronic test equipment

**Basic Shape Style:**

Rectangular or square

**Inclosure Type:**

Encased

**Operating Control Method:**

Manual

**Installation Design:**

Top of cabinet/counter

**Control Type:**

Local

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

0.0 megahertz operating channel and 50.0 megahertz operating channel

**Signal Voltage Rating Per Channel:**

10.000 volts output

**Pulse Duration Per Channel:**

0.00002 milliseconds operating channel and 200.00000 milliseconds operating channel

**Pulse Rise Time Per Channel:**

5.000 nanoseconds operating channel

**Pulse Decay Time Per Channel:**

5.000 nanoseconds operating channel

**Pulse Peak Amplitude Per Channel:**

10.000 volts operating channel

**Signal Data Type Per Channel:**

Operating channel pulse

**Output Wave Shape:**

Pulse, variable width and pulse, gate and pulse, trigger

**Operating Ac Frequency In Hertz:**

50.0 2nd voltage and 400.0 2nd voltage

**External Ac Operating Voltage In Volts:**

216.0 2nd voltage and 250.0 2nd voltage

**Special Features:**

Adjustable pulse upper and lower levels; selectable source impedance - 50 ohm termination; fixed ttl outputs; independent rate, width and delay control; four pulse outputs - fixed ttl level sync, ttl, ttl w bar over, and variable amplitude; full 10 volt output; 5 nanoseconds rise/fall times

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32200