NSN 6625-01-130-0046

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-130-0046
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
7.496 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.520 inches
Overall Width:
6.690 inches
Scale Division Quantity:
40 single indicator single range
Mounting Stud Length:
0.500 inches
Environmental Protection:
Humidity resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
5.760 inches
Meter Body Width Behind Mounting Flange:
4.885 inches
Movement Type:
Moving coil, permanent magnet

Background Color:

White single indicator single range

NSN 6625-01-130-0046

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+200.0 microamperes, dc single indicator single range
Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.240 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Special Features: Ruggedized
Ruggedized
Ruggedized Nuclear Hardness Critical Feature:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment Shelf Life:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment Shelf Life: N/a
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment Shelf Life: N/a
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment Shelf Life: N/a Unit Of Measure:
Ruggedized Nuclear Hardness Critical Feature: Nonhardened Surface Treatment: Enamel Style Designator: Rectangular flush mtg Fsc Application Data: Test set, electronic equipment Shelf Life: N/a Unit Of Measure: Demilitarization: