

View Online at <https://aerobasegroup.com/nsn/6625-01-131-0581>

Circuit Current For Which Designed:

Ac

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.406 inches

Overall Height:

4.406 inches

Overall Width:

4.406 inches

Scale Division Quantity:

80 single indicator single range

Mounting Stud Length:

0.625 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.500 inches

Meter Body Diameter Behind Mounting Flange:

3.969 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+90.0/+130.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Rectifier type; 25 to 1000 hz; self contained

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0