

View Online at <https://aerobasegroup.com/nsn/6625-01-131-8586>

Circuit Current For Which Designed:

Dc

Overall Depth:

1.800 inches

Overall Length:

7.100 inches

Overall Width:

3.400 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Manual 1; test lead 2; 9 v btry 1; oper card 1; fuse 1; cal certificate 1

Indicator Type:

Digital display

Installation Design:

Hand held

Frequency Response Range:

+48.000/+450.000 hertz

Background Color:

Gray single indicator all ranges

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

3-1/2

Measurement Range:

+0.0/+750.0 volts, ac single indicator 14th range

Scale Selection Method:

Switch and terminal

Features Provided:

Electrical overload protection and internal battery accommodation and portable and warning feature

Criticality Code Justification:

Feat

Accuracy Rating:

Porm 5.0 pct of reading plus 5 digits single indicator 12th range

Display Color:

Black single indicator all ranges

Circuit Attachment Method And Quantity:

3 wire lead

Operating Voltage Rating In Volts:

9.0 dc

Special Features:

Critical appl-trans; radar set, an/tps-32; tac air opn cntl, an/tyq-2

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Hand-held

Unit Of Issue Cube:

0.025 cubic feet

Supplementary Features:

Visual and audible continuity; peak-hold; level detection; conductance; diode test

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0