NSN 6625-01-134-8155

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-134-8155

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Dustproof
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; lockwasher 5; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Daniel
Panel
Mounting Arrangement Style:
Mounting Arrangement Style:
Mounting Arrangement Style: Three hole/stud bolt circle
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Power Source:

NSN 6625-01-134-8155 Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+75.0 amperes, dc single indicator single range
Scale Selection Method:
Switch
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/5 government specification
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A310a0