

View Online at <https://aerobasegroup.com/nsn/6625-01-138-1642>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2500.0

Overall Length:

4.094 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Scale Division Quantity:

60 single indicator single range

Mounting Stud Length:

0.625 inches

Environmental Protection:

Watertight

Furnished Items And Quantity:

Nut 8; washer 12

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.812 inches

Meter Body Diameter Behind Mounting Flange:

3.830 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+600.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Magnetic shield and shatterproof glass and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Sign on rear of case; band on scale from 360 v ac mark to 480 v ac mark

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0