

View Online at <https://aerobasegroup.com/nsn/6625-01-138-3845>

Circuit Current For Which Designed:

Dc

Overall Length:

2.160 inches

Overall Height:

Between 0.750 inches and 0.781 inches

Overall Width:

1.935 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

50.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.380 inches

Meter Body Width Behind Mounting Flange:

Between 1.812 inches and 1.843 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clip

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+15.0 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

Between 0.750 inches and 0.781 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0