

View Online at <https://aerobasegroup.com/nsn/6625-01-139-3744>

**Circuit Current For Which Designed:**

Ac

**Scale Division Quantity:**

32 single indicator 1st range

**Furnished Items And Quantity:**

Nut 6; lockwasher 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Top scale: 0; 1; 2; 3; 4; 5; 6; bottom scale: 0; 5; 10; 15; 20

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0