NSN 6625-01-141-5674

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-141-5674

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.245 inches and 2.255 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 2.245 inches and 2.255 inches

Overall Height:

3.120 inches

Overall Width:

3.270 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.620 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.130 inches

Meter Body Diameter Behind Mounting Flange:

2.790 inches

Movement Type:

Moving coil, permanent magnet

NSN 6625-01-141-5674

Voltmeter - Page 2 of 2



Background Color: White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External **Mounting Facility Type And Quantity:** 4 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized **Special Markings:** On back, sealed do not open Material: Plastic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A310a0