

View Online at <https://aerobasegroup.com/nsn/6625-01-144-3003>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

3.075 inches

**Mounting Stud Length:**

0.785 inches

**Overall Diameter:**

2.291 inches

**Distance Between Mounting Facility Centers:**

0.750 inches

**Furnished Items And Quantity:**

Nut 4; washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.761 inches

**Meter Body Diameter Behind Mounting Flange:**

2.054 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+10.0/+16.0 volts, dc single indicator single range

**Mounting Stud Diameter:**

0.188 inches

**Features Provided:**

Self-illumination facility and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Batt, at left end of scale; chg at right end

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0