

View Online at <https://aerobasegroup.com/nsn/6625-01-144-3003>

Circuit Current For Which Designed:

Dc

Overall Length:

3.075 inches

Mounting Stud Length:

0.785 inches

Overall Diameter:

2.291 inches

Distance Between Mounting Facility Centers:

0.750 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.761 inches

Meter Body Diameter Behind Mounting Flange:

2.054 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+10.0/+16.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.188 inches

Features Provided:

Self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Batt, at left end of scale; chg at right end

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0