

View Online at <https://aerobasegroup.com/nsn/6625-01-146-2009>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

3.133 inches

**Mounting Hole Diameter:**

0.126 inches

**Scale Division Quantity:**

11 single indicator single range

**Overall Diameter:**

2.684 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Nut 3; lockwasher 3; seal 1

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+375.000/+425.000 hertz

**Dial Scale Marking Color:**

White single indicator single range

**Resonant Reed Quantity:**

11

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.365 inches

**Meter Body Diameter Behind Mounting Flange:**

2.169 inches

**Movement Type:**

Vibrating reed

**Background Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+375.0/+425.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0