

View Online at <https://aerobasegroup.com/nsn/6625-01-147-4742>

**Case Material:**

Steel

**Maximum Voltage Rating In Volts:**

115.0 ac

**Inclosure Type:**

Partially enclosed

**Terminal Location:**

Front

**Power Source:**

External

**Mounting Method:**

Panel and rack

**Features Provided:**

Listen volume control and power light and power on-off switch

**Terminal Type And Quantity:**

69 jack

**Maximumlength:**

15.700 inches

**Maximumwidth:**

19.000 inches

**Maximumheight:**

10.100 inches

**Intelligence Data Handling Capability:**

Electrical frequency receiving automatic and electrical frequency receiving manual

**Indication Method:**

Receiving dial

**Phase:**

Single

**Special Features:**

Go/no-go self test; provides for monitoring of processor under test

**Frequency In Hertz:**

50.0 or 60.0 or 400.0

**Functional Description:**

Used for checkout and bench tests of cm-480a/apr-39v and c-10412a/apr-39v

**Supplementary Features:**

Reset button, rewind button, elapsed time dial, pass-fail self test button, test select buttons, bite address select, signal select, and df select switches

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A31700