

View Online at <https://aerobasegroup.com/nsn/6625-01-147-9894>

**Overall Length:**

525.0 millimeters

**Overall Height:**

210.0 millimeters

**Overall Width:**

315.0 millimeters

**Current Type:**

Ac and dc

**Frequency Rating:**

60.0 hertz

**Accessory Components And Quantity:**

Probe packages 1; crt filter 1; pair test leads 1; 1 amp agc fast-blow fuse 2; 0.5 amp agc fast-blow fuse 1; accessory pouch 1

**Voltage Rating:**

115.0 volts

**Beam Quantity:**

1

**Graduation Interval:**

Graduated lots/div both axes

**Screen Size:**

8 by 10 mm/div

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Included

**Sweep Circuit Type:**

Horizontal

**Sweep Frequency Range:**

+0.0/+100.0 megahertz

**Single Trigger Sweep Duration:**

0.5 microseconds and 5.0 microseconds

**Trigger Sweep Voltage Amplitude Rating:**

Between 50.0 millivolts and 150.0 millivolts

**Trigger Sweep Polarity Switch:**

Included

**Trigger Sweep Marker Intervals:**

1.25 s/div

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

5.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter

**Horizontal Deflection Sensitivity Voltage Rating:**

5.0 millivolts cw megahertz and 5.0 volts peak megahertz

**Input Intensity Modulation Feature:**

Provided

**Visual Modulation Sensitivity Voltage Rating:**

Between 5.0 millivolts and 5.0 volts

**Plate Direct Connection Deflection Sensitivity Provision:**

Provided

**Direct Connection Vertical Deflection Sensitivity Voltage Rating:**

5.0 volts any acceptable megahertz

**Direct Connection Horizontal Deflection Sensitivity Voltage Rating:**

5.0 volts peak to peak per centimeter

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

2.0 megahertz

**Y-axis Frequency Response Rating:**

100.0 megahertz

**Z-axis Frequency Response Rating:**

20.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Z-axis Input Impedance Rating:**

1.0 megohms

**Calibrated Screen Scale:**

Included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g