

View Online at <https://aerobasegroup.com/nsn/6625-01-148-7880>

Circuit Current For Which Designed:

Ac

Overall Length:

6.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches

Overall Height:

4.500 inches

Overall Width:

4.625 inches

Scale Division Quantity:

95 single indicator all ranges

Mounting Stud Length:

0.562 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

5.375 inches

Meter Body Diameter Behind Mounting Flange:

2.625 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-50.0 to 250.0 degrees fahrenheit single indicator 2nd range

Mounting Stud Diameter:

0.156 inches

Circuit Attachment Method And Quantity:

5 screw

Operating Voltage Rating In Volts:

115.0 ac

Extra Long Reference Number:

53-6104-0030-503r-scalem50p250f-100-ohm-rtd-typi

Special Markings:

Silver band between scale ranges; ten minus zero and five plus one hundred on first scale range

Material:

Plastic

Style Designator:

Rectangular flush mtg

Reference Number Differentiating Characteristics:

As specified by mrc elm

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0