

View Online at <https://aerobasegroup.com/nsn/6625-01-148-7880>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

6.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.625 inches

**Overall Height:**

4.500 inches

**Overall Width:**

4.625 inches

**Scale Division Quantity:**

95 single indicator all ranges

**Mounting Stud Length:**

0.562 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

5.375 inches

**Meter Body Diameter Behind Mounting Flange:**

2.625 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-50.0 to 250.0 degrees fahrenheit single indicator 2nd range

**Mounting Stud Diameter:**

0.156 inches

**Circuit Attachment Method And Quantity:**

5 screw

**Operating Voltage Rating In Volts:**

115.0 ac

**Extra Long Reference Number:**

53-6104-0030-503r-scalem50p250f-100-ohm-rtd-typi

**Special Markings:**

Silver band between scale ranges; ten minus zero and five plus one hundred on first scale range

**Material:**

Plastic

**Style Designator:**

Rectangular flush mtg

**Reference Number Differentiating Characteristics:**

As specified by mrc elm

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0