NSN 6625-01-151-8096

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-151-8096

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

6.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.050 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

Overall Height:

1.520 inches

Overall Width:

6.690 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.910 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 6; lockwasher 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

20.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.760 inches

Meter Body Width Behind Mounting Flange:

4.885 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

NSN 6625-01-151-8096

Special Scale Meter - Page 2 of 2



Pointer Color: Black single indicator single range Scale Marking: 0; 10; 20; 30; 40; 50; 60; 70; 80; 90; 100; f Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range **Mounting Stud Diameter:** 0.190 inches Meter Body Height Behind Mounting Flange: 1.240 inches **Features Provided:** Zero adjuster **Criticality Code Justification:** Astw and mark and feat **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized; weapon system essential **Special Markings:** F is marked at the side of number on scale 50 Material: Plastic Surface Treatment: Paint **Special Test Features:** Complies with mil-m-10304 Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A310a0