

View Online at <https://aerobasegroup.com/nsn/6625-01-154-2430>

Circuit Current For Which Designed:

Dc

Overall Length:

2.104 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.741 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches

Overall Height:

3.491 inches

Overall Width:

3.504 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.500 inches

Shortest Horizontal Distance Between Mounting Centers:

1.390 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.227 inches

Meter Body Diameter Behind Mounting Flange:

2.729 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+800.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0