

View Online at <https://aerobasegroup.com/nsn/6625-01-155-8857>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

6.030 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.050 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.725 inches

**Overall Height:**

1.520 inches

**Overall Width:**

6.690 inches

**Scale Division Quantity:**

30 single indicator single range

**Mounting Stud Length:**

0.910 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

5.760 inches

**Meter Body Width Behind Mounting Flange:**

4.885 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Lb per sq in. Gage 0 to 30 psig

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Meter Body Height Behind Mounting Flange:**

1.240 inches

**Criticality Code Justification:**

Feat

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Red line from 0 to 21 psig

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0