

View Online at <https://aerobasegroup.com/nsn/6625-01-155-8860>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

6.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.050 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.725 inches

Overall Height:

1.520 inches

Overall Width:

6.690 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.910 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.760 inches

Meter Body Width Behind Mounting Flange:

4.885 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Lb per sq in. Gage 0 to 100 psig

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.190 inches

Meter Body Height Behind Mounting Flange:

1.240 inches

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Red line from at 70 psig

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0