NSN 6625-01-156-1478

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-156-1478

| Circuit Current For Which Designed: |
|--|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 1.859 inches |
| Overall Height: |
| 2.234 inches |
| Overall Width: |
| 1.609 inches |
| Environmental Protection: |
| Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and |
| water resistant |
| Furnished Items And Quantity: |
| Nut 3; lockwasher 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Sensitivity Rating: |
| 18.0 volts |
| Dial Scale Marking Color: |
| Red single indicator single range and white single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 0.968 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.359 inches |
| Movement Type: |
| Moving magnet |
| Background Color: |
| Black single indicator single range |
| Pointer Color: |
| Orange single indicator single range |
| Scale Marking: |
| 8; 18 |
| Mounting Facility Type And Quantity: |
| 1 bezel and 1 bracket |
| Scale Graduation Type: |

Zero adjuster

Features Provided:

Nonlinear single indicator single range

NSN 6625-01-156-1478

Arbitrary Scale Meter - Page 2 of 2



| Movement Suspension Method: |
|---|
| Metal pivot base |
| Circuit Attachment Method And Quantity: |
| 3 threaded stud |
| Special Features: |
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Paint |
| Special Test Features: |
| Complies with mil-m-10304 |
| Style Designator: |
| Fan shape flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |