

View Online at <https://aerobasegroup.com/nsn/6625-01-156-7586>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2600.0

**Overall Length:**

11.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

Between 4.250 inches and 4.750 inches

**Overall Width:**

Between 4.250 inches and 4.750 inches

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Mounting Stud Length:**

Between 0.500 inches and 0.750 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 8; washer 8

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

5.0 amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

9.000 inches

**Meter Body Diameter Behind Mounting Flange:**

3.969 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Mounting Stud Diameter:**

0.125 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Phase:**

Three

**Special Features:**

Ruggedized, voltage is 400 hz

**Material:**

Plastic

**Special Test Features:**

Conforms to mil-m-16034a; mil-s-901

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Elec, elect. Properties measuring and test instruments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0