## NSN 6625-01-156-9679

Ammeter - Page 1 of 2

4 threaded stud

**Scale Graduation Type:** 

Nonlinear single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-01-156-9679

Circuit Current For Which Designed:
Ac
Overall Length:
2.219 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
1.750 inches
Overall Width:
3.062 inches
Mounting Stud Length:
0.500 inches
Barrel Width:
2.875 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.750 inches
Meter Body Width Behind Mounting Flange:
2.875 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:

## NSN 6625-01-156-9679

Ammeter - Page 2 of 2



Measurement Range:
+0.0/+50.0 amperes, $% \left( 1\right) =0.00000000000000000000000000000000000$
Mounting Stud Diameter:
0.112 inches
Scale Selection Method:
Terminal
Meter Body Height Behind Mounting Flange:
2.375 inches
Meter Barrel Depth:
1.750 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg barrel, down
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0