

View Online at <https://aerobasegroup.com/nsn/6625-01-157-2246>

**Circuit Current For Which Designed:**

Dc

**Overall Depth:**

1.800 inches

**Overall Length:**

7.100 inches

**Overall Width:**

3.400 inches

**Indicator Type:**

Digital display

**Installation Design:**

Hand held

**Power Source:**

Internal

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

4-1/2

**Measurement Range:**

+0.0/+750.0 volts, root mean square single indicator 3rd range

**Scale Selection Method:**

Switch

**Features Provided:**

Internal battery accommodation and electrical overload protection

**Accuracy Rating:**

Porm 2 pct of reading plus 3 digits single indicator 1st range

**Display Color:**

Black single indicator all ranges and gray, light single indicator all ranges

**Circuit Attachment Method And Quantity:**

3 banana jack

**Operating Voltage Rating In Volts:**

9.0 dc

**Special Features:**

Includes manual y8132 test leads, 9v battery, operator's card, spare fuse, statement of calibration practice; overload protection 500v dc or rms ac; frequency mode has autoranging, measures down to 12 hz, and will measure to 700khz in extended frequency mode; includes diode test function

**Style Designator:**

Hand-held

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0