

View Online at <https://aerobasegroup.com/nsn/6625-01-159-6446>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.560 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

40 single indicator single range

**Overall Diameter:**

3.500 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Transducer 1; nut 4; washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-0.25/+0.25 at 1/2 scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.380 inches

**Meter Body Diameter Behind Mounting Flange:**

2.760 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+360.0/+440.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Operating Voltage Rating In Volts:**

Between 105.0 ac and 135.0 ac

**Special Features:**

Freq transducer and matched meter are serialized to identify a matched pair

**Special Markings:**

Red band from 360 to 390 hz and from 410 to 440 hz; green band from 390 to 410 hz

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium and chromate

**Special Test Features:**

Conforms to mil-m-10304/12

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Transducer has two screw term. Ea of two sides

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0