

View Online at <https://aerobasegroup.com/nsn/6625-01-160-3224>

Circuit Current For Which Designed:

Dc

Overall Length:

2.600 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches

Overall Height:

6.410 inches

Overall Width:

7.690 inches

Scale Division Quantity:

15 single indicator all ranges

Mounting Stud Length:

0.410 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

449.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-0.5/+0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.160 inches

Meter Body Diameter Behind Mounting Flange:

2.790 inches

Movement Type:

Moving coil, permanent magnet

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+300.0/+450.0 milliamperes, dc single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

3 binding post

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0