

View Online at <https://aerobasegroup.com/nsn/6625-01-160-3224>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.600 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.500 inches

**Overall Height:**

6.410 inches

**Overall Width:**

7.690 inches

**Scale Division Quantity:**

15 single indicator all ranges

**Mounting Stud Length:**

0.410 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

449.0 millivolts

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-0.5/+0.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.160 inches

**Meter Body Diameter Behind Mounting Flange:**

2.790 inches

**Movement Type:**

Moving coil, permanent magnet

**Pointer Color:**

Black single indicator all ranges

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+300.0/+450.0 milliamperes, dc single indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

3 binding post

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0