

View Online at <https://aerobasegroup.com/nsn/6625-01-162-6191>

Circuit Current For Which Designed:

Ac

Overall Depth:

14.600 inches

Overall Height:

3.500 inches

Overall Width:

8.500 inches

Frequency Rating:

Between 40.0 hertz and 400.0 hertz

Furnished Items And Quantity:

Line cord 1; test leads; instruction/service manual 1; ieee-488 quick reference guide 1; instrument performance record

Indicator Type:

Digital display

Installation Design:

Bench

Power Source:

External

Display Type:

Light emitting diode

Display Digit Quantity:

5-1/2

Measurement Range:

+0.0/+200.0 volts single indicator 4th range

Scale Selection Method:

Switch

Accuracy Rating:

Porm0.004 pct of reading plus 2 digits single indicator 2nd range

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Interface Compatibility:

ieee-488

Special Features:

Temperature range 0 degrees c to 50 degrees c operating, minus 40 degrees c to plus 70 degrees c storage; humidity range 80 pct rh 0 to 35 degrees c, 70 pct to 50 degrees c; warmup time 1 hour to rated specs

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Portable w/tilt view handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0