

View Online at <https://aerobasegroup.com/nsn/6625-01-163-8230>

Circuit Current For Which Designed:

Ac

Frequency Rating:

Between 49.0 hertz and 500.0 hertz

Environmental Protection:

Dustproof and shock resistant and vibration resistant

Indicator Type:

Digital display

Installation Design:

Panel

Power Source:

External

Display Type:

Light emitting diode

Display Digit Quantity:

4

Measurement Range:

+0.0/+39.9 volts single indicator 2nd range

Scale Selection Method:

Terminal

Accuracy Rating:

Porm 0.15 pct of reading plus or minus 1 digit at 25 degrees c single indicator all ranges

Display Color:

Red, light single indicator all ranges

Circuit Attachment Method And Quantity:

3 screw

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Functional Description:

Used for true rms power measurements, complex waveform analysis, audio service equipment, standby power generators, modulation instrumentation

Supplementary Features:

Operating temp m 10 degrees c to p 60 degrees c; storage temp m 25 degrees c to p 85 degrees c; relative humidi type 0 to 95 pct non condensing; snap off optical filter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0