

View Online at <https://aerobasegroup.com/nsn/6625-01-163-8994>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1300.0

Overall Length:

1.563 inches

Overall Height:

2.750 inches

Overall Width:

2.750 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

1.500 inches

Furnished Items And Quantity:

Nut 8; clamp 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.625 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+300.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

External shunting

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Sign on rear of case

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instrument

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0