

View Online at <https://aerobasegroup.com/nsn/6625-01-166-3796>

Overall Length:

16.800 inches

Overall Height:

5.200 inches

Overall Width:

16.600 inches

Environmental Protection:

General purpose

Individual Section Quantity:

1

Operating Temperature Range:

+0.0/+55.0 degrees celsius

Average Life Measurement:

Indefinite

Basic Shape Style:

Rectangular or square

Identification Designator:

214bh01-28480

Inclosure Type:

Encased

Operating Control Method:

Automatic or manual

Installation Design:

Top of cabinet/counter

Control Type:

Local or remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

1.0 megahertz 6th output channel err-100 and 10.0 megahertz 6th output channel err-100

Frequency Adjustment Type:

Continuous

Signal Voltage Rating Per Channel:

0.300 volts output and 100.000 volts output

Impedance Rating Per Channel:

50.000 ohms output channel

Pulse Duration Per Channel:

10.000 nanoseconds output channel and 25.000 milliseconds output channel

Pulse Rise Time Per Channel:

15.000 nanoseconds output channel

Polarity Per Channel:

Positive output channel err-100

Pulse Repetition Rate Per Channel:

Jgbaar10.000 and 99.999 kilopulses per second 4th output channel err-100

Pulse Peak Amplitude Per Channel:

100.000 volts output channel

Signal Data Type Per Channel:

Output channel pulse

Output Wave Shape:

Pulse, gate and pulse, variable width

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, coaxial front

Operating Ac Frequency In Hertz:

48.0 single voltage and 66.0 single voltage

Connection Contact Type And Quantity:

3 receptacle, coaxial external

External Ac Operating Voltage In Volts:

240.0 4th voltage

Special Features:

Special triggering output

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200